HPLC Application

ID No.: **20146**

Isoxsuprine on Lux 5µm Cellulose-4 in RP

Column: Lux® 5 µm Cellulose-4, LC Column 250 x 4.6 mm, Ea
Dimensions: 250 x 4.6 mm ID
Order No: 00G-4491-E0
Elution Type: Isocratic
Eluent A: MeOH / 20mM NH4HCO3 (60:40) DEA (0.1%)

Gradient Profile:	**Step No.**	**Time (min)**	**Pct A**
	1	0	100

Flow Rate: 1 mL/min
Col. Temp.: ambient
Detection: UV-Vis Abs.-Variable Wave.(UV) @ 220 nm (ambient)
Analyst Note: SecurityGuard™ Guard Cartridge System extends column lifetime.

- SecurityGuard Cartridges, Lux Cellulose-4 4 x 3.0 mm, 10/Pk Part No.: AJ0-8627
- Holder Part No.: KJ0-4282

Products used in this application:



ANALYTES:

1 Isoxsuprine
Retention Time: 19.36 min

2 Isoxsuprine
Retention Time: 26.57 min

©2025 Phenomenex Inc. All rights reserved.

For more information contact your Phenomenex Representative at support@phenomenex.com

Phenomenex products are available worldwide.